

ULTRALUBE® E-338/3

Product Description:

Ultralube® E-338/3 is a water based cationic paraffin wax emulsion improving the surface qualities of aqueous leather lacquers and leather finishes.

Ultralube® E-338/3 can also be used for water proofing of building materials.

Technical Data:

Form supplied	: white liquid
Solids type	: paraffin wax
Solids content	: 50% ± 1
pH	: 4.0 ± 0.5
Ionic character	: cationic
Melting range	: ~ 35-56°C

Processing:

Ultralube® E-338/3 is stirred directly into the formulation.

Long storage might cause a phase separation because of different density of water and paraffin.

Please stir before use!

Dosage:

3-6% in reference to the entire formulation

Properties:

Ultralube® E-338/3 is used in:

- * leather lacquers
- * leather finishes

in order to increase or improve:

- * water repellency
- * soft touch
- * slip
- * anti blocking

Ultralube® E-338/3 is also used in concrete for water proofing.

Packaging:

- 110 kg drum - 900 kg IBC - tank car

Storage / Transport:

This product is stable for at least twelve months at temperatures of 5°C to 30°C.

!! Keep from freezing and temperatures higher than 30°C !!

Transport Classifications:

For further information please refer to the material safety data sheet.

EEC-Labeling Requirements:

For further information please refer to the material safety data sheet.

FDA-/BfR-Regulations:

FDA : please inquire

BfR : please inquire

issue date: 14.03.2017
edition/supersedes: 01/17
revision: 0

All information given here are based on our own research or the research of others and believed to be accurate and shall give the user guidance for the application. Nevertheless these data are no specification and due to the versatile possible formulations, applications, processings and further parameters at the formulator/user the usage of this product has to be tested carefully in the particular system/application by the formulator/user. All information mentioned here are not warranted properties. There is no responsibility of the seller if the material is used outside the recommended field of use; any liability, also for any patent infringement, cannot be derived from this.