

ULTRALUBE[®] E-360

XP-11090755

Product Description:

Ultralube[®] E-360 is a water based wax emulsion improving the surface qualities of lacquers and leather coatings. Ultralube[®] E-360 can also be used in floor polishes as well as for modified latex coatings.

Technical Data:

Form supplied

Solids type Solids content pH Ionic character Melting range : light brown transparent to opaque liquid
: modified paraffin wax
: 25% ± 1
: 9.0 ± 0.5
: anionic
: ~ 56-85°C

Properties:

Ultralube[®] E-360 is used in:

- * wood stain and varnishes for wood-work based on acrylic-, acrylic/PUR and alkyl emulsions
- leather coatings

Processing:

Ultralube[®] E-360 is stirred directly into the formulation.

Dosage:

3-8 % in reference to the entire formulation

in order to increase or improve:

- slip
- * anti blocking
- * water resistance
- scratch resistance
- * a silky feel

Packaging:

- 120 kg drum - 1000 kg IBC - tank car

Storage / Transport:

This product is stable for at least six months at temperatures of $5^{\circ}C$ to $30^{\circ}C.$

!! Keep from freezing and temperatures higher than 30°C **!!**

Transport Classifications:

For further information please refer to the material safety data sheet.

EEC-Labelling Requirements:

For further information please refer to the material safety data sheet.

FDA-/BfR-Regulations:

FDA	: please	inquire

BfR : please inquire.

issue date: 03.02.2012 edition/supersedes: 02/12 / ML revision: 0

All information given here are based on our own research or the research of others and believed to be accurate and shall give the user guidance for the application. Nevertheless these data are no specification and due to the versatile possible formulations, applications, processings and further parameters at the formulator/user the usage of this product has to be tested carefully in the particular system/application by the formulator/user. All information mentioned here are not warranted properties. There is no responsibility of the seller if the material is used outside the recommended field of use; any liability, also for any patent infringement, cannot be derived from this.

keim additec surface GmbH Hugo-Wagener-Straße 9 D-55481 Kirchberg/Hunsrück Tel. +49 (0) 6763/9333 – 0 Fax +49 (0) 6763/9333 – 30

Geschäftsführer: Helmut Keim information@keim-additec.de www.keim-additec.de Steuernummer: 40/662/0185/2 USt-IdNr.: DE 148083246 Handelsregister: Amtsgericht Bad Kreuznach HRB Nr. 2440



DIN EN ISO 14001.2005



DIN EN ISO 9001 2008