

ULTRALUBE® MD-2007

Product Description:

Ultralube® MD-2007 is a water based micro dispersion free of emulsifier based on a special wax compound improving the surface qualities of different types of aqueous coatings and polishes.

Ultralube® MD-2007 can also be used for the production of water based deforming lubricants.

Technical Data:

Form supplied	: milky brownish liquid
Solids type	: wax compound
Solids content	: 35% ± 1
pH	: 8.5 ± 0.5
Ionic character	: slightly anionic
Melting range	: ~80-110°C

Processing:

Ultralube® MD-2007 is stirred directly into the formulation.

Stir well before use!

Dosage:

3-8% in reference to the entire formulation

Properties:

Ultralube® MD-2007 is used in:

- * wood lacquers
- * wood stains
- * leather lacquers

Ultralube® MD-2007 is also used in:

- * polishes
- * car care products

in order to increase or improve:

- * mar and scuff resistance
- * slip
- * abrasion resistance
- * anti blocking
- * silky feel

in order to increase or improve:

- * good buffability
- * water repellency
- * high durability

Packaging:

- 120 kg drum - 1000 kg IBC - tank car

Storage / Transport:

This product is stable for at least twelve months at temperatures of 5°C to 30°C.

!! Keep from freezing and temperatures higher than 30°C !!

Transport Classifications:

For further information please refer to the material safety data sheet.

EEC-Labeling Requirements:

For further information please refer to the material safety data sheet.

FDA-/BfR-Regulations:

FDA : please inquire

BfR : All raw materials used in Ultralube® MD-2007 fulfil the requirements of BfR XIV and XXXVI.

issue date: 10.03.2017
edition/supersedes: 09/16
revision: 4

All information given here are based on our own research or the research of others and believed to be accurate and shall give the user guidance for the application. Nevertheless these data are no specification and due to the versatile possible formulations, applications, processings and further parameters at the formulator/user the usage of this product has to be tested carefully in the particular system/application by the formulator/user. All information mentioned here are not warranted properties. There is no responsibility of the seller if the material is used outside the recommended field of use; any liability, also for any patent infringement, cannot be derived from this.