

mju:wax® 2300

Product description micronised wax compound EINECS: preparation

mju:wax® 2300 is a micronised wax compound with PTFE.

| Characteristic | Unit | Target value |
|----------------------------------|-------------------|--------------|
| Appearance | - | white powder |
| Particle size (D ₅₀) | μ m | 6.5 |
| Particle size (D ₉₀) | μ m | 13 |
| Acid value | mg KOH/g | 0 |
| Density (23°C) | g/cm ³ | 1.07 |

Major fields of application

mju:wax[®] 2300 is a micronised wax additive used in solvent based can and coil coatings as well as powder coatings to provide excellent slip and scratch resistance.

Packaging

Paper-bags of 20 kg netto.

Storage

The product has to be stored dry at room temperature.

Beware of sunlight and heat.

Stability at least 2 years from date of delivery.

Hazards

This product does not require labelling in terms of preparation guideline. Further security relevant data see safety data sheet.

Ecology/toxicology properties

The product is water insoluble. Further information see material safety data sheet.

Status under food legislation

The product fulfills legislations of various countries. More details on request.

All information given here are based on our own research or the research of others and believed to be accurate and shall give the user guidance for the application. Nevertheless these data are no specification and due to the versatile possible formulations, applications, processings and further parameters at the formulator/user the usage of this product has to be tested carefully in the particular system/application by the formulator/user. All information mentioned here are not warranted properties. There is no responsibility of the seller if the material is used outside the recommended field of use; any liability, also for any patent infringement, cannot be derived from this.

version 1.0 11.05.2013