

SILCO AF 865

Product Description:

SILCO AF 865 is a silicone emulsion for efficient defoaming and deaerating of water based coating systems especially for OPV.

Technical Data:

Form supplied:	white emulsion
Total solids:	40 ± 1%
Active agent:	high molecular silicone polymers
Ionic character:	non ionic
pH-Value:	8,0-10,0
Dosage:	Recommended level is 0.1 – 1.0% on formulation

Properties:

SILCO AF 865 is used in

- industrial pigment preparations
- OPV
- printing inks

with

- highly efficient defoaming

and

- deaerating properties
- high persistency
- shear stable

Special notes:

Silco AF 865 is stable for at least 12 months at room temperature.

Please avoid temperatures under 4°C and over 40°C.

Prevent from freezing! Stir before use!



FDA-/BfR-Rules:

FDA: available on request

BfR: available on request

Safety and MSDS :

For regulatory details such as the classification and labelling as dangerous substances or goods please refer to our corresponding Material Safety Data Sheet.

Packaging:

- 30 kg hobbock

- 60 kg hobbock

- 120 kg drum

This leaflet gives the user guidance and information but does not claim to be complete and is without any obligation.

revision: 2/PS
issue date: 2013-5-21
issued by : 05/13 EA