

SILCO AF 700

Product Description:

SILCO AF 700 is a solvent- and APEO-free deaerator for waterbased, solventbased and UV coatings

Technical Data:

Form supplied : opaque liquid
Total solids : > 95%
Active agent : siloxane ester
 blended with silica
Ionic character : not applicable
pH-Value : not applicable
Processing : Add to the coating system
 by stirring.
Dosage : Recommended level is
 0.1 - 1.0% on formulation

Properties:

SILCO AF 700 is used for

- * high viscous (UV)screen inks
- * 2 or 3 K epoxy flooring systems

in order to

- * release existing foam of high viscous coating systems
- * prevent foam formation at high shear rates

Storage:

SILCO AF 700 is stable for at least 12 months at room temperature. Please avoid temperatures under 4°C and over 40°C.

!Prevent from freezing!

FDA-/BfR-Rules:

FDA : available on request

BfR : available on request

Transport Classifications:

ADR. : refer to MSDS

IMCO : refer to MSDS

UN-NR : refer to MSDS

EEC-Labeling Requirements:

Symbol : refer to MSDS

R-S : refer to MSDS

S-S : refer to MSDS

Packaging:

- 25 kg hobbock
- 200 kg drum
- 1000 kg IBC

This leaflet gives the user guidance and information but does not claim to be complete and is without any obligation.

revision: 2
issue date: 15-12-2010
issued by : DL