

SILCO AF 844

Product Description:

SILCO AF 844 is a silicone emulsion for efficient defoaming and deaerating of waterbased coating systems

Technical Data:

Form supplied : white emulsion
Total solids : 26 ± 1%
Active agent : high molecular silicone polymers
Ionic character: nonionic
pH-Value : 7,0-9,0

Dosage : Recommended level is
0.3 - 1.0% on formulation

Properties:

SILCO AF 844 is used in

- * industrial pigment preparations
- * wood coatings/furniture lacquers
- * high build transparent coatings
- * printing inks
- * leather finishes and coatings

with

- * highly efficient defoaming and deaerating properties
- * high persistency

Storage:

Please avoid temperatures under 4°C and over 40°C.

!Prevent from freezing!

FDA-/BfR-Rules:

FDA : available on request

BfR : available on request

Transport Classifications:

ADR. : not classified
IMCO : not classified
UN-NR : not classified

EEC-Labeling Requirements:

Symbol : not applicable
R-S : not applicable
S-S : S-25

Packaging:

- 30 kg hobbock
- 60 kg hobbock
- 120 kg drum

This leaflet gives the user guidance and information but does not claim to be complete and is without any obligation.

revision: 1
issue date: 2010-11-26
issued by : 11/10 EA