

SILCO WET C-602

Product Description:

Silicone based high performance wetting agent for solventbased coating systems

Technical Data:

form supplied	: clear liquid
active ingredient	: modified polysiloxane
total solids	: >98%
solvents	: none
ionic character	: nonionic
pH-Value	: not applicable
Processing	: SILCO WET C-602 is added with stirring to the coating formulation
Dosage	: 0.1 – 0.5% based on the whole formulation. The product can be prediluted in organic solvents in order to simplify the dosing and mixing.

Properties:

SILCO WET C-602 is used as high performance additive in solventbased

- * printing inks
- * industrial coatings
- * paint formulations

in order to improve

- * the surface slip
- * the leveling, wetting and gloss
- * anti-cratering

Storage:

SILCO WET C-602 is stable for at least two years at room temperature. Please avoid temperatures under 0°C and over 50°C.

FDA-/BfR-Rules:

FDA	: please contact us
BfR	: please contact us

Transport Classifications:

ADR.	: refer to MSDS
IMCO	: refer to MSDS
UN-NR	: refer to MSDS

EEC-Labeling Requirements:

Symbol	: refer to MSDS
R-S	: refer to MSDS
S-S	: refer to MSDS

Packaging:

- small sizes on demand
- 20 kg hobbock
- 200 kg drums
- 1000 kg container

This leaflet gives the user guidance and information but does not claim to be complete and is without any obligation.

Revision: 0/DL
Issue date: 24.January 2012