

ULTRALUBE® WL-717

Product Description:

Ultralube® WL-717 is a wax dispersion improving the surface qualities of aqueous and solvent based lacquers.

Technical Data:

Form supplied	: tan liquid
Solids type	: wax compound
Solids content	: 30% ± 1
Melting range	: >113°C (wax)
Solvent	: 2-butoxyethanol
Ionic character	: nonionic
Particle size	: ~2-4 µm (average)

Processing:

Ultralube® WL-717 is stirred directly into the formulation.

Stir well before use!

Dosage:

0.5-5 % in reference to the entire formulation

Properties:

Ultralube® WL-717 is used in:

- * can coating lacquers (inside and outside)
- * coil coating
- * leather top coats

in order to increase or improve:

- * slip
- * mar and scuff resistance

Packaging:

- 100 kg drum

Storage / Transport:

This product is stable for at least twelve months at temperatures of 5°C to 30°C.

!! Keep from freezing and temperatures higher than 30°C !!

Transport Classifications:

For further information please refer to the material safety data sheet.

EEC-Labeling Requirements:

For further information please refer to the material safety data sheet.

FDA-/BfR-Regulations:

FDA : please inquire

BfR : please inquire

issue date: 10.03.2017
edition/supersedes: 09/16
revision: 3

All information given here are based on our own research or the research of others and believed to be accurate and shall give the user guidance for the application. Nevertheless these data are no specification and due to the versatile possible formulations, applications, processings and further parameters at the formulator/user the usage of this product has to be tested carefully in the particular system/application by the formulator/user. All information mentioned here are not warranted properties. There is no responsibility of the seller if the material is used outside the recommended field of use; any liability, also for any patent infringement, can not be derived from this.