

LORY VISCOSITY CUP

VF2199

DATASHEET

PRODUCT DESCRIPTION

The TQC Lory Cup is designed for quick measurements on location or during production processes. The bottom of this cup is provided with a small hole and needle point. The product measured will flow out of the small hole and as soon as the needle point appears during this process, the flow time is determined.

**BUSINESS**

Coating Laboratories, Paint Production

FEATURES

- Ideal for quick testing
- Each cup provided with unique serial number
- Easy to clean

SCOPE OF SUPPLY

- TQC lory cup

ORDERING INFORMATION

VF2199 – TQC Lory cup

SPECIFICATIONS

Material cup: brass, zinc plated
Cup handle : steel
Size : 170x49 mm
Weight : 130g

USE

1. Dip the TQC Lory cup in to the liquid to be measured. Twist several times to avoid any bubbles which may be clinging to the internal surface of the Lory cup.
2. Now stir the liquid gently to make sure density and temperature are equal.
3. Leave the Lory cup in the liquid for about 1 to 5 minutes
4. Now remove the Lory cup vertically, and start your stopwatch the moment the top of the cup breaks the surface of the liquid.
5. The liquid will flow out of the small hole in the bottom of the cup. In the mean time check the surface of the product within the Lory cup, as soon as the needle point appears you must stop your stopwatch.
The flow time is now determined.



SPECIAL CARE

- Always clean the instrument after use.
- Clean the instrument using a soft dry cloth. Never clean the instrument by any mechanical means such as a wire brush or abrasive paper. This may cause, just like the use of aggressive cleaning agents, permanent damage.

DISCLAIMER

The right of technical modifications is reserved.

The information given in this sheet is not intended to be exhaustive and any person using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. Whilst we endeavour to ensure that all advice we give about the product (whether in this sheet or otherwise) is correct we have no control over either the quality or condition of the product or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing to do so, we do not accept any liability whatsoever or howsoever arising for the performance of the product or for any loss or damage (other than death or personal injury resulting from our negligence) arising out of the use of the product. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.